

Zinc Alloy(KZA3) for Die Casting

Standard Specification (%)		Typical Assay (%)	
Aluminium(Al)	3.9~4.2		4.05
Magnesium(Mg)	0.04~0.05		0.045
Copper(Cu)	0.0012 max		0.0010
Lead (Pb)	0.0030 max		0.0026
Iron(Fe)	0.0050 max		0.0041
Cadmium(Cd)	0.0010 max		0.0005
Tin(Sn)	0.0010 max		0.0005
Nickel(Ni)	0.0010 max		0.0005
Silicon(Si)	0.0200 max		0.0020
Zinc(Zn)	Remainder		Remainder

Form and Packing	
Slab Weight(kg)	8±0.5
Slab Dimensions(mm)	115x460x30
Bundle Weight(kg)	960±60
Bundle Dimensions(mm)	460x920x520
Slabs per Bundle(EA)	Regular Slab 112 Foot Slab(8kg)x8

Standards
ASTM B240-AG40A
JIS H2201 Zinc Alloy Class 2
KS D2311 Zinc Alloy Class 2



Zinc

Lead

Precious Metals and Others

Chemicals

HAI AU DEVELOPMENT CO.,LTD

114 Than Nhan Trung St., Ward 13, Tan Binh Dist., HCMC, Vietnam.
 Hotline: 028.38106701 Email: info@haiaucorp.com.vn
 Website: www.haiaucorp.com.vn