

# Zinc Alloy(KZA5) for Die Casting

Standard Specification (%)		Typical Assay (%)	
Aluminium(Al)	3.9~4.2		4.05
Magnesium(Mg)	0.035~0.06		0.047
Copper(Cu)	0.7~1.1		0.9
Lead(Pb)	0.003 max		0.0026
Iron(Fe)	0.005 max		0.0043
Cadmium(Cd)	0.002 max		0.0005
Tin(Sn)	0.001 max		0.0005
Nickel(Ni)	0.001 max		0.0005
Silicon(Si)	0.020 max		0.0020

Form and Packing	
Slab Weight(kg)	8±0.5
Slab Dimensions(mm)	115x460x30
Bundle Weight(kg)	960±60
Bundle Dimensions(mm)	460x920x520
Slabs per Bundle(EA)	Regular Slab 112 Foot Slab(8kg)x8

Other alloys by this mould "KZA" are produced on customer order base.

Uses
Automobiles
Industrial Machinery and Tools
Electric Devices
Communication Equipments
Toys and Leisure Goods
Precision Instruments
Home Appliances
Defence Equipments



Zinc

Lead

Precious Metals and Others

Chemicals

## HAI AU DEVELOPMENT CO.,LTD

114 Than Nhan Trung St., Ward 13, Tan Binh Dist., HCMC, Vietnam.  
 Hotline: 028.38106701 Email: info@haiaucorp.com.vn  
 Website: www.haiaucorp.com.vn