

# Electrolytic Lead

Ingot type Standard Specification (%)		Typical Assay (%)	
Lead(Pb)	99.995 min		99.9980
Silver(Ag)	0.0008 max		0.0003
Copper(Cu)	0.0005 max		0.0001
Iron(Fe)	0.0002 max		0.0001
Bismuth(Bi)	0.0015 max		0.0013
Arsenic(As)	0.0005 max		0.00005
Antimony(Sb)	0.0005 max		0.00005
Zinc(Zn)	0.0002 max		0.00005
Tin(Sn)	0.0005 max		0.00005
Nickel(Ni)	0.0002 max		0.00005
Cadmium(Cd)	0.0002 max		0.00001
Tellurium(Te)	0.0001 max		0.00008

LME Registered Brand

Ingot type Form and Packing	
Slab Weight(kg)	26±1.5
Slab Dimensions(mm)	550x80x70
Bundle Weight(kg)	1,090±70
Slabs per Bundle(EA)	42

Jumbo Type Form	
Dimensions(mm)	590x590x300
Weight(kg)	900±50

Uses
Storage Battery Pastes
Lead Litharge Solder
Radiation Shielder
Cable Sheathing
Pigment Colors
Weight and Ballast
Bearings
Ammunition

